



PRODUCT SPECIFICATION

ORYKTO

2465 BOUL. FORD
CHÂTEAUGUAY QC J6J 4Z2, CANADA

+1-438-497-8089 | INFO@ORYKTO.CA
WWW.ORYKTO.CA

ULTRA-LITE PLYWOOD

For **effortless handling** and **superior lightness**, ULTRA-LITE plywood is the ideal choice. It is made from **Falcata wood**, which ensures its **reduced weight**. Being about **half the weight of traditional plywood**, it's perfect for projects where reducing weight, enhancing performance, or improving fuel efficiency is crucial—all without compromising on quality.

SIZES

DIMENSIONS

2440 MM X 1220 MM (4'X8')

THICKNESS/PLY

9 MM	12 MM	15 MM	18 MM
5/7 PLY	7 PLY	7/9 PLY	9 PLY



TECHNICAL PROPERTIES	UNIT	VALUE
Density	Kg/m ³	360 to 400 ± 10%
Glue Application	-	Type II, E-1 (CARB Phase II/EPA)
Moisture Content	%	10% to 20%
Temperature of Hot Pressing	°C	100°C - 110°C
Finishing	-	Well Sanded
Dimensional Tolerances		
Thickness	mm	+/- 0.5 mm